

## INDUSTRIAL SOLUTIONS PRODUCT CATALOGUE

























www.industrialsolution.ae



#### **YOUR INDUSTRIAL PARTNER**

#### **DUBAI HEAD OFFICE**

PO BOX 19227, Dubai - United Arab Emirates

Tell: +971 4347 4444

Email: info@mef.ae | industrial@mef.ae

Web: www.mef.ae | www.industrialsolution.ae

#### Branches 🛑

<u>es</u> 🔽

Abu Dhabi Sharjah Fujairah

Ras Al Khaimah

#### SAUDI ARABIA 🥮

Jeddah Dammam Riyadh

#### **OTHER GCC**

Qatar



Oman





#### Middle East Fuji LLC

Middle East Fuji LLC is a subsidiary company of Fuji Trading Co, Ltd. Japan and is among the leading Marine supply, Engineering & Industrial products / services provider in the Middle East. We represent various leading manufacturers of Marine & Industrial products as agent and distributors in the Middle East

#### **Facilities & Services**

- Head office & main warehouse (over 100,000 Sq Feet) located in Al-Quoz Industrial Area Dubai.
- Equipment Sales and Services
- Stock of wide range of Industrial Equipment and Spare Parts.
- Branch offices at Abu Dhabi, Fujairah, Ras Al Khaimah, Doha, Muscat, Salalah, Jeddah, Dammam and Riyadh
- Over 300 Skilled & experienced staff.
- Comply with ISO 9001 2015 standard with total computerized operation (ERP Solution).
- Availability of Training room & repair facility.
- Own Fleet of transporting trucks.













MOBILITY SUSTAINABILITY CREATIVITY

MEF's Vision is to 'Be the Best Service Provider in the Region', as measured by Customer Satisfaction, Quality of Service, Financial Profitability, Growth and high standards of Health & Safety.

We represent various reputed manufacturers of quality industrial equipment. with a team of factory trained sales engineers & technicians we support our customers both on site & at our facilities with sales & rental fleet of equipment.





**One-touch cutter replacement Coolant into the Heart of the cut Built-in motion sensor Fail-safe restart** Magnet open-circuit sensor

Slow start mechanism **Auto-feed Load sensor Variable speed** Cycle stop **Overload stop** 



Very fast mounting and removing of cutters, with different size of cutters available.



WA-5000

LOAD DETECTOR







Max. plate thickness 75 mm













Model		QA-4000	QA-6500	WA-3500	WA-5000	AO-5575	WOJ-3200	A-100	LO-3550				
		Fu <b>ll</b> Aut	tomatic	Automatic			Ma	nual					
Power source (Single Pha	se)			220-240VAC, 50/60 Hz									
Power Consumption		Watt	680	1,010	1,100	1,150	1,150	950	1,600	800			
Electric Drill No Load Speed RPI		RPM	750	400/750	950	350/650	350/650	870	330	950			
Magnet Power Consumption Watt		Watt	50	75	34	75	50	70		35			
Max. Cutting Capacity	Hole Dia.	mm	40	65	35	50	55	32	100	35			
Max. Cutting Capacity	Plate Th.	mm	35	50	35	75	75	50	75	50			
Magnet Holding Power		N	6,664	9,800	7,056	9,800	10,000	9,000	17,640	5,500			
Overall Dimentsions WxD	хH	mm	215 x 407 x 535	215 x 455 x 535	237 x 409 x 535	237 x 425 x 613	86 x 296 x 611	99 x 318 x 361	318 x 705 x 575	65 x 316 x 280			
Magnet Dimensions WxD		mm	82 x 172	100 x 200	92 x 216	101 x 201	86 x 170	99 x 177	130 x 256	65 x 145			
Weight		Kg	18.5	26	20	23	18	13	50	8.7			








Optional One-Touch Adapter Optional one touch adapter allows the use of up to 13mm twist drills to be used in the orginal

Features/Model	QA-4000	QA-6500	WA-3500	WA-5000	A0-5575	WOJ-3200	A-100	LO-3550
Overload Stop	✓	✓	✓	✓	✓	✓	✓	✓
One-touch Cutter Replacement	✓	✓	✓	✓	✓	✓		✓
Fail-Safe Restart	✓	✓	✓	✓	✓	✓		✓
Magnet Open-Circuit Sensor	✓	✓	✓	✓	✓	✓		✓
Integrated Cooling Tank	✓	✓	✓	✓	✓		✓	✓
Built-in Motion Sensor	✓	✓	✓	✓				
Slow Start Mechanism	✓	✓	✓	✓				
Automatic Feed	✓	✓	✓	✓				
Variable Speed Adjustment	✓	✓	✓	✓				
Cycle Stop	✓	✓	✓	✓				
Auto Return	1	✓						

#### **Quick Autos: Reduce Drilling Time!**

Because of Nitto's automatic-feed mechanism, total drilling time is 30% less than older style manual feed magnetic drills. Our automatic drills constantly monitor resistance on the cutter and adjust feed rates accordingly. Ultimately holes are cut as quickly and efficiently as possible while maintaining cutter





QA-4000

**Optional** Chip Breaker





NILLO KOHKI

#### **Portable Hydraulic Puncher**

New design adopted for punching steel, stainless steel. Punching round or elongated holes on steel plates, H-beam steel, framework, and on-site punching holes on shaped steels.





HS11-1624

Portable punchers and

punching. Full punching cycle is

pumps are ideal for on-site

automated after the start

Inching function (manual

operation) is also available.

button is depressed.

Max. Throat Depth

ng Time



HA11-1624



- Full punching cycle is automated after the start button is depressed.
- An emergency switch stops the punch instantly at any time.
- A special urethane spring is built-in to return the punch.

19

13

22

10.5

21.5



E55-0619

- Hydraulic pump and powermotor combination in a simple body for outstanding workability.







HPD-05 Double Acting Hydraulic pump

25

220-240VAC, 50/60

mm

Sec

Sec

1ph

Dia mm

Model		HPD-05	SC-05	
Power Source	Power Source 1ph			
Acting Mode		Double	Single	
Max. Output Pressure	bar	686.5		
At No Load	L/min	1.2		
Motor	Watt	400		
Reservoir Capacity	L	4		
Weight	kg	32.5	27.5	

E25-0615 | E55-0619 | HA06-1322 | HA07-1624 | HA11-1624 | HS06-1322 | HS07-1624 | HS11-1624

24

16.5

28.5

Single Acting Hydraulic Pump

110

16

24

16.5

35.5

•	No hydraulic hose,
	extremely small mounting
	space exactly fits the need:
	of worksite.

24

11.8

25.5

Double Acting Hydraulic Pump

24

11.8

5.7 25

30

13

22

7.9

20.5





Superior cold cut bevelling for straight, round, and orbital edges by portable, lightweight, and durable tools.

























Model			TIAND DEVEL		CINCOIT DEVELER		
		HB-158	EMB-0307C	MB-03A	ECB-0203	CB-02	
Power Source	50/60Hz		1PH, 22	Pneumatic			
Rated Power Consumption	Watt	910	1,010	430	450	0.4m3/min @5.9 bar	
Chamfering Capacity	Mild Steel	0C-15C	0C-7C, 2R, 3R, 4R	0C-3C, 2R, 3R	0C-3C, *2R, *3R	0C-2C, 2R	
Chairing Capacity	Stainless Steel	-	0C-3C, 2R, 3R, 4R	-	0C-1.5C, *2R	-	
Chamfer Angle		15°-45°	15°-45°	45°	45°	45°	
Weight	kg	15	3.9	2.5	2.5	1.8	
Remarks			Available in Pneumatic type				



Nitto Kohki's "Delvo" Electric Screwdrivers are high-quality tools for professional use, with special emphasis on precision torque control and long life.

They always apply just the correct amount of torque with accurate and positive control at your fingertips. They are smooth and shockless in operation too, with eco-friendly Brushless motor.



#### **AIR SONIC**

Pneumatic Die Grinders

Ergonomically designed pneumatic die grinders, work on all metals, wood, and plastics, even extremely hard and exotic materials.

Model	L-25B	L-35C	AL-55	
Rated Air Pressure	Bar	6	6	6
Air Consumption (No Load)	m3/min	0.4	0.35	0.17
Free Speed	rpm	27,000	37,500	56,500
Size of Collect Chuck	m/m	6	6	3
Hose Size	inch	1/4	1/4	1/4
Weight	kg	0.6	0.45	0.25





#### **JET CHISELS**

Powerful scaling with multi-needles.



Removal of spatter after welding, rough chipping concrete and stone slabs, work similar to sand blasting and shot blasting of castings and painted finishes, chipping welding slag, removing paint and rust from panels and sheet metal, and removal of other encrusted materials.





Model	JT-20	JC-16	JEX-24	JEX-28	
Rated Air Pressure	Bar	6	6	6	6
Air Consumption (No Load)	m3/min	0.2	0.15	0.27	0.35
Stroke Speed	rpm	4,000	4,000	4,000	4,500
Needler	mm	OD 3 x180	OD 2 x 150	OD 2 x 180	OD 3 x 180
Needles	IIIIII	(12pcs.)	(29pcs.)	(23pcs.)	(28pcs.)
Hose Size	inch	3/8	3/8	3/8	3/8
Weight	kg	2.4	1.4	2.7	3.5

Model	EJC-32A			
Power Source 1 PH		115 V AC 60 Hz	230 V AC 50 Hz	
Power Consumption	300			
Rated Current	Α	2.8	1.4	
Stroke Speed	min-1	3,000		
Needles	mm	OD 3 x 180 (15 pcs.)		
Power Cord	m	5		
Weight	kg	4	.5	


- Jet Chisel needles adjust to any surface contour automatically. They get deep into corners, all the way into uneven surfaces, and all types of curvatures.
- Hard steel needles blow at stroke speed of 4,000 4,500 per minute. (Pneumatic scaler)
- Side handle can be turned to any position in accordance with job positions. (Electric scaler)

#### **AIR CHIPPER**

Chipping after welding is EASY!

- Suitable for chipping after welding and removing solid substances adhered to the works at job sites.
- Easy chisel replacement is made to excellent operation.
- The straight grip-to-chisel design is suitable for operation in narrow or secluded area.

Model	ACH-16	CH-24	
Rated Air Pressure Bar		6	6
Air Consumption (No Load) m3/min		0.15	0.2
Stroke Speed	min-1	6,000	4,000
Size of Chisel Shank	mm	OD 10.5	12.7 WAF*
Hose Size	inch	3/8	3/8
Weight	kg	0.9	1.7









#### **BELTON**



The most versatile belt sander ever developed!

Bear grind-off, casting finish, furniture surface finish, plastic products profile adjustments, mold sanding & adjustment, spot weld head-off finish, die-cast finish, stamped sheet metal trimming & chamfering, and iron parts surface sanding.



Model		B-10CL	B-20 CL	B-20 CL-A	B-30 CL	
Air Pressure Mi	Pa (kgf/cm²)	0.6 (6)				
Air Consumption (No-load)	m³/min	0.4	0.4	48	0.82	
Free Speed	min-1(rpm)	17000	180	000	15000	
Belt Speed	m/min	1120 2770			2310	
Belt Size	mm	10 x 330	20 x	30 x 540		
Inlet Size		Rc 1/4				
Mass(Weight)	kg	0.9	1.6	1.5	2.4	

- Suitable for sanding and grinding in narrow spaces, recessed areas and on curved surfaces
- Quick belt change
- Rear exhaust system

#### **MYTON**

**Pneumatic Sanders** 

High performance yet quiet sanding.



Good for all kinds of sanding jobs especially in limited spaces or those require high sanding performance.

- Uses one-touch disc pads (MAS-20B)
- Ideal for sanding in tight spots (MAS-20B)
- High performance sander good with disc paper (MAS-40)

Model		MAS-20B	MAS-40
Rated Air Pressure	Bar	6	6
Air Consumption (No Load)	m3/min	0.4	0.45
Motor Free Speed	rpm	22,000	13,000
Abrasive Disk		OD 1", OD1-1/2" and OD 2"	OD 100 mm
Hose Size	inch	1/4	3/8
Weight	kg	0.5	0.9

#### **MYTON**

**Pneumatic Grinders** 

Deburring, cleaning and smoothing jobs typical at fabrication shops, foundries, refineries, shipyards, power plants and a variety of sites for other industries.

- All models are angle type mighty grinders with silencer.
- Available for light-duty to heavy-duty range of grinding work.




Model		MLG-25	MLG-40	MAGW-40	MAG-50	MAG-70
Rated Air Pressure	Bar	6	6	6	6	6
Air Consumption (No Load)	m3/min	0.42	0.45	0.68	0.87	0.75
Free Speed	rpm	19,000	13,000	13,000	12,000	7,600
Depressed Center Wheel	mm	OD 58	OD 100	OD 100	OD 125	OD 180
Hose Size	inch	1/4	3/8	3/8	3/8	3/8
Weight	kg	0.6	1.5	1.55	2.2	2.45

#### **POWER TOOLS**

#### **AUTO CHISEL - AIR HAMMER**









More chisel shapes are also available





S-1000

#### **AIR DRILL**

weight is 1.7 kg.



Pneumatic hand drill with Builtin silencer, reversible rotation switch, and variable speed adjustment.

Model	Model				
Rated Air Pressure	bar	6	6		
Air Consumption (No Load)	m3/min	0.55	0.67		
Free Speed	rpm	2,900	2,000		
Max. Drilling Capacity	mm	6.5	10		
Weight	kg	0.8	1.1		

#### **SUPER KELEN**

Pneumatic scaler, achieves labor savings in industrial, shipboard descaling and cleaning jobs.

Spring Balancer

- Removes solid substances such as rust and concrete adhered to mixer panels.
- Employ idle running proof structure with 2,500 rpm stroke high speed.
- Three types of bar length are available in accordance with applications.

	S-250	S-500	S-1000
Bar	6	6	6
m3/min	0.27	0.27	0.27
min-1	2,500	2,500	2,500
mm	OD 12.7	OD 12.7	OD 12.7
inch	1/4	1/4	1/4
mm	OD 630x49	OD 890x49	OD 1370x49
kg	4.1	4.7	6.1
	m3/min min-1 mm inch mm	Bar         6           m3/min         0.27           min-1         2,500           mm         OD 12.7           inch         1/4           mm         OD 630x49	Bar         6         6           m3/min         0.27         0.27           min-1         2,500         2,500           mm         OD 12.7         OD 12.7           inch         1/4         1/4           mm         OD 630x49         OD 890x49



#### **TIGON**

Improves work safety and efficiency.

#### **Retractors Sizes**

Model	RW-0	TW-1R	RW-3	RW-5
Capacity (kg)	0.5-1.5	0.5-1.5	1.0-3.0	2.5-5.0
Stroke (m)	2	1.5	2	2
Weight (kg)	0.50	0.40	0.70	0.90

#### Spring Balancers Sizes

Spring balai	icers size	'S										
Model	TW-00	TW-0	TW-3	TW-5	TW-9	TW-15	TW-22	TW-30	TW-40	TW-50	TW-60	TW-70
Capacity (kg)	0.5-1.5	0.5-1.5	1.0-3.0	2.5-5.0	4.5-9.0	9.0-15.0	15.0-22.0	22.0-30.0	30.0-40.0	40.0-50.0	50.0-60.0	60.0-70.0
Stroke (m)	0.5	1	1.3	1.3	1.3	1.3	1.5	1.5	1.5	1.5	1.5	1.5
Weight (kg)	0.50	0.60	1.60	1.70	3.90	4.30	8.10	8.70	10.60	11.30	12.20	12.70

Retractors





# Quick Connect Couplings



















Inert gas, Vacuum, Helium



Nitto Kohki's unique technologies and dedicated research have been proven by numerous patents, which led to the development of 25,000 different Cupla variations.

- Applications diversify from general household to high-tech industries such as in oceanic and space development.
- Diameters range from a tiny 1mm to a huge 540mm.
- Wide varieties of body materials such as steel, brass, plastic, aluminum or stainless steel are available.






Mold

Air Point

Oxy Fuel Cutting Torch





Some Applications


















Hose Reel.

Hose reels to transport fluid from a vertical point, the hose retracts back when released.











Fuji has manufactured tools for some of the toughest and most demanding industrial environments in Japan and on the planet. This has resulted in a wide range of robust and long lasting material removal tools that is the preferred choice for metalworking in Japan and many places overseas. Our range of assembly tools and error proofing solutions was born from the needs of the Japanese manufacturing industry and delivers quality and safety together with speed of operation and ergonomic handling.

#### **FA 20 SERIES ANGLE GRINDERS**

- Compact & Low head
- Powerful
- Low **Vibration**



#### FW - 330 SERIES IMPACT WRENCH

- Powerful
- Durable
- **Ergonomic**



#### **FLT \*3 SERIES SHUT-OFF PLUSE TOOLS**



- 3 Times Longer Service life
- High Torque Accuracy
- Low Noise/Vibration
- High Productivity
- Ergonomic Design

#### FRC-200S1-STEEL MILLING **MACHINE**



- 3 Times Faster than a grinder to flatten weld seam
- Preserve the working surface.
- Comfortable and easy to handle.







Cutting and beveling:

- high-alloy steel (stainless steel)
- low-and unalloyed steel
- plastics
- casting materials and
- non-ferrous metals in just seconds, using the "Planetary Cutting" technology.





Cutting thin-walled tubes and elbows using the superior "Planetary Cutting Technology".

Deformation-free clamping system by integrated clamping jaws made from coated cast aluminum.





New, innovative saw from Orbitalum Tools for cutting and beveling of tubes and elbows in just seconds. The perfect preparation for orbital welding!








Model		BRB2-Kit1	BRB2-Kit2	REB6	REB14	RPG2.5
Drive		Pneumatic	Pneumatic	Electrical	Electrical	Electrical
Power	kw	0.38	0.38	1.2	1.2	1
Speed	rpm	0-120	0-120	10-32	5-16	9-153
Power Supply	50/60Hz	NA	NA	1PH230V	1PH230V	1PH230V
Air Supply	m3/min	0.7	0.7	NA	NA	NA
Pipe ID	mm	12.75-25.5	19.1-46.0	49-159	92-320	-
Pipe OD	mm	16.75-41.5	23.0-62.0	56-168	100-355.5	6.35-63.5
Wall Thickness	mm	2 <b>-</b> 8	2-8	3 <b>-</b> 22	4 <b>-</b> 30	Max.3

Counterboring and axial turning of pipes made from high-alloy steel (stainless steel), low-alloy and carbon steel. Designed for pipe end preparation and boiler pipe applications.






#### Mobile Welder OC Plus

Portable orbital welding power source

The Mobile Welder OC Plus is the first portable orbital welding power source designed specifically for use on the construction site. The Mobile Welder OC Plus brings the usual high and consistent quality of orbital welding to even the most remote locations.

The lightweight and robust design is equipped with state-of-the-art information and communication technology and builds on the strengths of the Orbimat 180SW - our established Smart Welder.

- Simple.
- Portable.
- Modular.













300SW



The ORBIMAT CA advanced series of orbital welding power supplies are equipped with a new and unique operating concept.

In addition to the reliable automatic programming which generates welding parameters by entering the tube diameter, wall thickness, material, and welding gas all ORBIMAT CA models also have the exclusive new development FLOW FORCE to reduce the pre-flow gas time when the weld heads are closed in the standard model and BUP control function with controllable, position-dependent tube internal pressure control as an optional extra.



180SW



P16

TP 400

Model	from tube ID to Tube OD [mm]	Weight (kg)
Tube-to-Tube-Sheet p1	6 10 - 78	17.5

**76S** 

Model		Tube OD (mm)	Weight (kg)
Open weld head	TP 250	20 - 77	10.5
Open weld flead	TP 600	70 - 170	13.8
Closed weld head	76 S	6 - 77	9.0
Closed Weld Head	115	20 -115	20.7









#### **Diaphragm Pumps**

GRACO process equipment line includes air-operated double diaphragm pumps, peristaltic hose pumps, piston pumps and high pressure cleaning equipment for low to high viscosity fluids for a variety of aggressive applications.



Model	Saniforce	515	1040	1590	2150	1590 HS & 3-A	3150 HS & 3-A	Meat / Pou <b>l</b> try
Max Flow Rate	Lit/min	61	151	340	568	340	568	568
Max Fluid Pressure	bar	7	8	8	8	8	8	8
Suction Lift (Wet)	m	7.6	8.84	8.84	8.84	8.5	5.5	3
Max Pumpable Solids	mm	2.38	3.2	4.8	6.3	15.9	25.4	63.5
Max. Fluid Viscosity	cps	10,000	10,000	15,000	20,000	15,000	20,000	25,000





SaniForce 6:1 Sanitary Drum Unloader



The SaniForce 6:1
Sanitary Drum unloader features an on-demand workflow capability and can also be taken apart quickly for applications that require frequent sanitation. Available in double ball and priming pistion designs for additional system flexibility.

SaniForce 3150 Bin Evacuation System



The SaniForce 3150 bin evacuation system (BES) evacuates viscous products from their original 300gallon containers without diluting the material. Standard with an inflatable ram plate seal, the BES allows a quick replacement of the empty container. An all-pneumatic version is available for applications that do not require metering or batch control and an electronic version is available for those applications that do.





#### Introducing 3M<sup>™</sup> Cubitron<sup>™</sup> II Fibre Disc 982CX Pro

featuring re-engineered 3M Precision-Shaped Grain and redesigned construction.

## How the best get better.

### Boost productivity and your bottom line.

Introducing the new 3M<sup>™</sup> Cubitron<sup>™</sup> II Fibre Disc 982CX Pro and the new 3M<sup>™</sup> Pneumatic Angle Grinder and Pneumatic Sander. The new fiber discs that cut even faster and last even longer than our legendary Cubitron<sup>™</sup> II Fibre Discs. When paired with our tools and recommended back-up pads, the system gives you more power than ever before. It's performance, power and productivity optimized.

Cuts
33%
Faster

than Cubitron II Fibre Discs 982C

Introducing 3M™ Cubitron II Fibre Disc 982CX Pro

featuring re-engineered 3M Precision-Shaped Grain and edesigned construction.





#### **COATED AND BONDED ABRASIVES**

#### **3M** Abrasives

3M's experience of working in partnership with a wide range of industries has enabled us to develop a comprehensive range of abrasive solutions designed to deal with mild steel and stainless steel.



#### 3M<sup>™</sup> Flap Discs 769F Harness the power of 3M


Precision-Shaped Grain at a price that's affordable for everyday use.

- · Grinding, Beveling, Blending
- Finishing & surface prep
- Scale and weld spatter removal



#### 3M<sup>™</sup> Silver Depressed Centre Grinding Wheel, 51787

- Perfect for heavy grinding, beveling and weld removal
- 3M Precision Shaped Grain cuts cleanly and fast, helping to increase productivity
- Long-lasting wheel provides great performance value
- Use on a variety of substrates such as carbon steel and stainless steel
- Works with tools and accessories designed for depressed centre grinding wheels



- •Metal bond secures diamond particles for long-lasting performance
- •Premium low-stretch backing supports various grinding applications
- •Works well on a variety of materials: stone, glass, ceramic, metal carbide and composites
- •Open dot pattern allows swarf and debris to escape, helping to prevent loading









For more than 100 years, 3*M* has been a world leader in developing advanced Abra-sives products and systems. Some familiar brands include, Scotch-Brite, Wet-or-dry, Cubitron, Trizact, Roloc, Green Corps and Hookit. 3*M*™ offers innovative Abrasive solution for grinding, cutting, blending, sanding, dimensioning, cleaning, stripping, resurfacing, fluting, polishing or finishing.



982C

3M<sup>™</sup> Cubitron<sup>™</sup> II Fibre Disc 982C outperforms conventional ceramic industrial abrasive discs. Our discs feature 3M Precision Shaped Grain technology, offering up to twice the cut rate, durability and lifespan of conventional discs with less grinding pressure required.



782C

3M<sup>TM</sup> Fibre Disc 782C is a fibre disc engineered for an ultra-rapid cut on carbon steel. These discs feature our advanced abrasive technology, 3M Precision Shaped Grain. Their stiff fibre backing and strong resin bond provides durability and tear resistance. These discs are compatible with 3M disc pad face plates and hubs (sold separately).



51889

Scotch-Brite™ Clean and Strip XT Pro Extra Cut Disc utilizes aluminum oxide abrasive in an open nylon web to efficiently eliminate challenging coatings like heavy rust, thick paint, and corrosion. It swiftly removes these layers while also blending and refining the underlying bare metal. The disc's high conformability ensures a larger contact patch for a faster removal rate, making it effective in cleaning welds and restoring surfaces.



969F

3M<sup>™</sup> Cubitron<sup>™</sup> II Flap Disc 969F is made with layers of abrasive material. Our flap discs are unique in design and feature a fast cutting abrasive material on flaps of tough polyester cloth. These discs come with a grinding aid and semi-flexible, Y-weight, backing gives each flap excellent strength.





3M<sup>™</sup> Cubitron<sup>™</sup> II Hookit<sup>™</sup> Film Disc 775L features 3M<sup>™</sup> Precision Shaped Ceramic Grain a revolutionary advancement in abrasive technology. Our film discs can cut up to twice as fast and last up to six times as long as normal abrasives.

775L



3M<sup>TM</sup> Cubitron<sup>TM</sup> II Hookit<sup>TM</sup> Disc 950U is an abrasive disc designed to deliver high performance in body-in-white applications. It's powered by fast-cutting, long-lasting 3M Precision-Shaped Grain in a super-open-coat construction that resists loading with sanding swarf. The E-weight paper backing is specially designed for sanding metal.



Dust extraction meets industry-leading cut-rate in 3M Xtract<sup>TM</sup> Cubitron<sup>TM</sup> II Net Disc 710W. This premium sanding disc features a unique abrasive pattern on a net backing that allows for virtually dust-free sanding, with legendary 3M<sup>TM</sup> Precision-Shaped Grain technology. You'll finish more parts per disc with less dust in the environment, boosting productivity without sacrificing worker health.



Scotch-Brite™ General Purpose Hand Pad 7447 combines flexible fibers with outstanding cut to help you accomplish tough cleaning jobs or produce fine finishing results, use after use. it is a superior alternative to steel wool, wire brushes, sandpaper, and other non-woven products for cleaning or finishing tasks.

7447



Scotch-Brite™ Roloc™ Surface Conditioning Disc combines our durable, non-woven disc with the efficient Roloc quick-change attachment system, for effective cleaning, finishing, blending and deburring. These discs use non-woven fibre which conforms well to irregular surfaces.

SM

#### 3M™ Random Orbital Sander, Xtract Pneumatic 88958, 6"

This helps in delivering high-quality surface preparation and finishing results with your 3M<sup>TM</sup> Abrasives.

- SELF-GENERATED VACUUM (SGV): Uses the inlet air to create its own venturi vacuum that extracts the dust from the work surface and expels it through a wide collection port on the back of the tool into a filter bag
- POWERFUL AND PRECISION-BALANCED 209W MOTOR.
- APPLICATIONS: Metal fabrication, primer sanding, gelcoat sanding, composite sanding, and woodworking.
- PART OF THE 3M XTRACT CLEAN SANDING SOLUTIONS: When used with 3M Xtract Net Discs and dust extraction, the system extracts up to 97% of the dust created during sanding.





3M<sup>™</sup> Speedglas<sup>™</sup> Welding Safety


## Do your best with our best welding helmets

#3MScienceofSafety



#### What do you need?

#### Full-featured helmet with the maximum number of options



9100xx

9100

9002NC

G5 07 series

### 3M versaflo<sup>TM</sup>

## Powered air Purifying Respirators


Facility Maintenance, Grinding, Sanding, Machine Operations, Powder Handling, Pharmaceutical



Versaflo<sup>™</sup> PAPR TR

300 600 800





## When the heat is on, stay strong.



Take on the most demanding high temperature applications with the new 3M™ VHB™ Tape GPH series.

#### 3M™ VHB™ Tape GPH Series

The new 3M™ VHB™ Tape GPH series is a permanent bonding solution that can replace traditional mechanical fasteners and liquid adhesives in challenging, high temperature applications. It uses a conformable, acrylic foam core to provide a good balance of strength and conformability. The 3M™ VHB™ Tape GPH series has exsellent temperature resistance, making it ideal for permanent bonding where high temperature tolerance is needed, including applications that undergo a powder coat or liquid painting process.

#### **Features**

- Good adhesion to high and medium surface energy materials (metals, glass, plastics) as well as many coated or painted surfaces
- Excellent temperature resistance (short term 450°F and long term 300°F)
- Good solvent resistance
- High initial tack providing strong immediate handling strength
- Conformable foam offers good gap filling and stress relaxation



Jumeirah Beach Hotel, Dubai UAE Curtain wall design: Aluminum panels bonded to steel stiffeners.

Burj Al Arab Hotel, Dubai UAE Aluminum composite panels bonded to framework to resist high wind loads.



Product Description		Product Number	Thickness	Spec	ification		Length	Color	Application / Features
3M™VHB™ TAPES FOR GENERAL PURPOSE HIGH TEMPERATURE APPLICATIONS	6	GPH 160	1.6mm	12.7mm	19.05mm	25.4mm	33m	GRAY	SIGNAGE, MOUNTING APPLICATIONS, STIFFENER APPLICATION,
		GPH110	1.1mm	12.7mm	19.05mm	25.4mm	33m	GRAY	CAN GO THROUGH POWDER COATING PROCESS
3M™ VHB™ STRUCTURAL GLAZING TAPES – VHB™ SGT		B23F	2.3m	12.7mm	19.05mm	25.4mm	33m	BLACK	GLASS BONDING ON UCW PANELS, STRUCTURAL GLAZING, INTERIOR GLAZING
3M™ VHB™TAPES FOR CLADDING, STIFFENERS AND ARCHITECTURAL PANELS – VHB™ AGT	9	4941P	1.1mm	12.7mm	19.05mm	25.4mm	33m	GRAY	CLADDING, PANEL STIFFENER BONDING, GLASS PANELING, WOODEN CLADDING, METAL AND PLASTIC BONDING, BONDING HIGH AND MEDIUM SURFACE ENERGY SUBSTRATES
3M™ VHB™ FIRM TYPE FOAM CORE TAPE	0	4950P	1.1mm	12.7mm	19.05mm	25.4mm	33m	WHITE	ALTERNATIVES TO RIVETTING OR WELDING, METAL BONDING, MOUNTING & TRIM ATTACHMENT, PANEL TO FRAME/STIFFNER TO PANEL ASSEMBLY
3M™ VHB™ - CLEAR TAPE		4910P	1.0mm	12.7mm	19.05mm	25.4mm	33m	CLEAR	JOINING TRANSPARENT MATERIAL, MOUNT BACKLITTRANSLUCENT SIGNS, EDGE-BOND RESIN FILLED GLASS, METAL, GLASS AND HIGH SURFACE ENERGY (HES) SUBSTRATES, DÉCORATIVE MATERIAL AND TRIM, NAMEPLATES AND LOGOS, PANEL TO FRAME, STIFFENER TO PANEL.
3M™ VHB™ MODIFIED ACRYLIC ADHESIVE CONFORMABLE ACRYLIC FOAM CORE TAPE	9	5952P	1.1mm	12.7mm	19.05mm	25.4mm	13.7m	BLACK	DECORATIVE MATERIAL AND TRIM, NAMEPLATES AND LOGOS, ELECTRONIC DISPLAYS, PANEL TO FRAME, STIFFENER TO PANEL
3M™ EXTREME SEALING TAPE 4412N IS A TRANSLUCENT, HIGHLY CONFORMABLE, SINGLE-SIDED, PRESSURE SENSITIVE ACRYLIC ADHESIVE TAPE WITH A HIGH PERFORMANCE IONOMER BACKING	0	4412N	2.0mm	50.8mm	101.6mm		16.5m	WHITE	TRUCK AND TRAILER ROOF SEALING, WINDOW AND DOOR SEALING, HVAC, JOINTS AND SEAMS, GUTTERS
3M™ PRIMER 94 - ADHESION PROMOTER FOR BETTER BOND STRENGTH	SMA Protect bill	PRIMER 94		US Quar	t - 946 m <b>l</b>			CLEAR L <b>I</b> GHT YELLOW	PROMOTE BETTER ADHESION FOR A VARIETY OF PLASTIC SURFACES SUCH AS POLYETHYLENE, POLYPROPYLENE, ABS AND PET \ PBT BLENDS
3M™VHB™ TAPE UNIVERSAL PRIMER UV,	-	UV PRIMER 94		US Qua	rt - 946 m <b>l</b>			LIGHT YELLOW WITH FLUORESCENT BLUISH TINT	ADHESION PROMOTER, LOW VOC , UV-INDICATOR VERIFIES PRIMER APPLICATION, QUICK DRY TIME



#### Smooth Sided (3M™ VHB™ Tape) vs. Mechanically-Fastened





Applying 3M™ VHB™ Tapes



Extreme sealing tape




Dynamic normal tensile and elongation tests: Quantifies the internal cohesive strength of  $3M^{\text{\tiny TM}}$  VHB  $^{\text{\tiny TM}}$  Tape and allows the elongation of  $3M^{\text{\tiny TM}}$  VHB  $^{\text{\tiny TM}}$  Tape to be compared to that of adhesives. Unlike mechanical fasteners and traditional assembly methods, the viscoelastic foam core of  $3M^{\text{\tiny TM}}$  VHB  $^{\text{\tiny TM}}$  Tape absorbs tensile stress, distributing the stress across the entire bond, isolating the stresses by allowing them to move independently, while maintaining a strong bond.















3M™ Gasket Adhesive 1300L









3M™ VHB™ Tapes and Adhesives-Industries















#### **Disposable Respirators**



**3M**<sup>™</sup>8210 Disposable Respirator (N95) \* Features welded strap attachment, soft nose foam and adjustable noseclip to help proivde a custom fit and secure seal



**3M**<sup>™</sup>8835 Disposable Respirator, FFP3, Valved, 8835+ Premium disposable P3 respirator offering relisble, effective protection against dust, mist & metal fume.



**3M**<sup>™</sup>FT-10 uses a test solution of sodium saccharin that produces a sweet tasting aerosol



**3M**<sup>™</sup>8511 Disposable Respirator (N95) \*Is uniquely designed to help provide protection

against certain non-oil based particles

\* Designed to help deliver classic N95 Respiratory protection with the addition of the proprietary 3M Cool Flow Valve



**3M**<sup>™</sup>8247 Disposable Respirator (R95) Non-valved Specialty Respirators: Suggested Application: Grinding, bagging, sanding, sweeping in oil and non-oil environments and other dusty operations.



**3M**<sup>™</sup>FT-30 uses a test solution of denatonium benzoate to produce a bitter tasting aerosol

#### **Reusable Respirators**



3M<sup>™</sup> 6000 / 6502 / 6800 / FF 402 Series Reusable Respirator Provides Lightweight, Easy-to-use, **Economical Protection** 



3M<sup>™</sup> Organic Vapor Cartridge 600,1 6006 / 6007 /60926, 6005, EA / Case



3M<sup>™</sup> Particulate Filter 2091/2097/7093c/P100



3M™ Acid Gas Cartridge 6002



3M™ Multi Acid Gas/Organic Vapor Cartridge 6006



3M™ Reusable Respirator 7500 Series 3M<sup>™</sup> Organic vapor/Acid Gas Cartridge 6003/07047 3m Half Facepiece Respirators 7500 Series, Reusable Provides Comfortable, Soft Silicone Faceseal





#### **Hearing Protection**



3M™ Foam Earplugs



Carrying Case

3M™ E-A-R Ultra Fit Earplugs 340 / 4002 / 4004



3M™ E-A-R Classic Earplugs 310-1001







3M™ One Touch™ Pro Earplug Dispenser



3M™PELTOR Optime 98 Earmuffs H9A



3M™ E-A-Rfit Dual- Ear Validation Systam



3M<sup>™</sup> PELTOR Optime 105 Earmuffs H10B, Behind-the-Head



KOVAX is the leading Manufacturer of Japanese Coated Abrasives since 1930. Our rigid quality control and well organized manufacturing facilities, and advanced technical knowledge ensures top quality and innovative abrasive products for Automotive, Wood-working, and many more industrial uses.



Water Proof Abrasive paper

Grit Ranges

Silicon Carbide: P60-P2000

Aluminium Oxide: P120-P2000





Kovax TRI-PRO Super Tack Disc is made of advantage experience of our sanding technology that we pursue fine uniform finish from aggressive cutting force and long paper life, and of course purse-friendly.

Available Grit: P60, P80, P100, P120, P150, P180, P220, P240, P280, P320, P360, P400, P500, P600



Kovax DRY Super Buflex sanding system used as final sanding step before polishing in various surface such as high solid/hard paint, fluorine clear, anti-scratch clear, water paint and more.

Available Grit: P2000, P2500 & P3000



Mini Polisher KP-301 (Part No.9100301)

Light-weight and easy operation belt sander, Precision-build and durable body made in Japan. Small size but efficient sanding.

Specification Pad Size : 40mm or 70mm or 98mm,

Rotation Speed : 2,500 rpm , Weight : 0.70kgs.



Belt Sander 10/12mm KB-504

Light-weight and easy operation belt sander, Precision-build and durable body made in Japan. Small size but efficient sanding.

Specification: Rotation Speed: 17,000rpm, Weight: 0.93kg,.

Abrasive Belt: 10 (12) mm x 300mm



PROTECTION - FROM HEAD TO TOE, IN THE WORKPLACE

A SEGMENTATION FOR DESIGNING PRODUCTS AND RANGES:



KNOW THE RISKS



ANALYZE THEM
IN THE WORKERS'
ENVIRONMENT AND





TOOL: SEGMENTAT**I**ON



CONSTRUCTION
OF A SUITABLE
PRODUCT OFFER











Our multi key input segmentation (business areas, risks, levels of range) is the foundation on which is built the strategy of the range and future products are determined and designed, which meet the constraints and risks in the workplace.



HEAD PROTECTION
HAND PROTECTION
DISPOSABLE WEAR
WORKWEAR
OUTDOOR WEAR
TECHNICAL WEAR
FOOT PROTECTION
FALL PROTECTION

THE GLOBAL OFFER

#### • THE BUSINESS AREAS

<b>6</b>	AGRICULTURE/ GREEN AREAS	Farmers - Woodcutters - Gardeners .			Logistics - Transportation - Airport - Distribution
1	CONSTRUCTION/ CMIL ENGINEERING	Structural work - Construction		HYGIENE ENVIRONMENT	Food industry - Pharmacy - Hospitals - Restaurants - Communities
Ä	SECOND WORK/CRAFTSMAN	Electricians - Plumbers - Heating specialists - Painters	<u>₩</u>		Petrochemical industry - Refinery - Off shore - Exploration - Pipelines
	HEAVY INDUSTRY	Metal construction - Petrochemical	<b>=</b>	MINING	Mines (exploration, extraction) -Stone-pit
444	LIGHT INDUSTRY	Automotive - Aerospace - Industrial Subcontracting	#	WIND ENERGY	













**DIAMOND V** 

**QUARTZ UP IV** 

**MAGNY HELMET 2** 

**BARRIER 2** 

CASOUD3

BALBI2













**BRAVA** 

FUJI 2

**TOBA3 T5** 

**GALERAS** 

**INTERLAGOS FOLDABLE** 

SPA 3













M1300VC

M1200VC

M1195B

**ALUCAG19A** 

H0600

DT117

















VV910

VECUT44

VECUT55

**VE733** 

VE712GR

**TOUTRAVO 509** 

VV905







**JET3 S1P SRC** 



**ASTI S1P SRC** 



**BROOKLYN S3 SRC** 



SAGA S3 SRC







MIAMI



**KAZAK EH** 



**KALINKA** 



TW 400

#### **RESCUE HUB TC063 KIT WALTC114**

DESCENDER, RESCUE AND LIFTING EQUIPMENT WITH HAND WHEEL ABLE TO LIFT UP TO 225KG. APPROVED FOR 2 PEOPLE, AUTOMATIC BRAKE SYSTEM. 2 CENTRIFUGAL BRAKE SYSTEMS.



#### **CARGO LASHING**

Cargo Lashings from 1 to 4 width with lashing capacities ranging from 360kg to 5000kg



#### **BODY PROTECTION**

#### High visibility vests







#### Winter Jackets



















## Ansell







11-801 / 11-840 Improved design delivers enhanced comfort in a dirt masking color

Ansell's HyFlex® 11-801 gloves are ideal for dry or slightly oily applications that require light mechanical protection and high levels of handling finesse.

They are well-suited to light assembly applications as well as to the needs of logistics and warehousing.



48-203
Heavy Duty Impact Protection

The EDGE® 48-203 Heavy Duty Impact glove with a PVC dot palm provides excellent protection against impact hazards with enhanced grip that resists oil, making it the go-to glove in the Oil & Gas industry.

Bright yellow ensures that hands are visible at all times.



48-305 / 48-920
Medium duty general pupose industrial gloves

EDGE® 48-305 industrial work gloves are the economical solution for medium weight applications requiring a good level of abrasion resistance along with a good grip in dry or wet environments.

This is also the economical choice for use in a wide range of handling and carrying applications, and are more durable than medium weight cotton or leather gloves.



- Mechanical
   Heat resistant
   Cut resistant
   Anti vibration
- •Chemical resistant •Impact resistant •Disposable •Electrical insulating









The MICROFLEX™ 92-134 disposable nitrile examination glove offers tactility and comfortable protection across numerous applications. The lightweight, soft and stretchy nitrile formulation offers a comfortable fit and feel with the tactile sensitivity needed for fine motor control. Designed with textured fingertips for secure handling of tools and materials. Testing with NA medical team.





08-354

Neoprene dipped coating on an interlock knit liner

Ansell 08-354, liquid-proof industrial gloves offer a rough finish dip that makes handling wet, slippery materials easier and safer. These Neoprene liquid-proof industrial gloves are extremely comfortable to wear.



AlphaTec Solvex®

37-675 / 37-676

Excellent chemical protection with a good level of grip, fit and comfort

AlphaTec Solvex 37-675 industrial gloves' cotton flocking absorbs sweat, for greater wearer comfort.

Their nitrile composition offers these AlphaTec gloves greater resilience than neoprene or rubber equivalents of a similar thickness, with EN and ANSI level 4 abrasion resistance. The safety gloves are suitable in both wet and dry conditions





ActivArmr 43-216 is a heat-resistant industrial glove, fortified for advanced hand protection in demanding tasks. The three-dimensional thumb design enhances dexterity and control. Durability and comfort thanks to premium leather and Kevlar® welded seams. Long cuffs with cotton lining Increases forearm and wrist protection





43-217
Welder thermal heat protection

ACTIVARMR® 43-217, Heavy-duty TIG welding gloves, combining thermal hand protection and dextrorotatory tactility

Excellent thermal and welding capabilities. with three-dimensional thumb design For highly precise welding gloves. Enhanced durability thanks to premium full-grain goatskin and welded seams.

Suitable for TIG welding, as well as grinding, brazing, metal fabrication and maintenance. Extra protection against heat, flames, sparks and welding spatter.



87190 Extra thin natural rubber glove for excellent sensitivity

ALPHATEC® 87-190 87-190, Extra-fine natural latex gloves, offering excellent tactile sensitivity for light tasks. 100% cotton flock lining: Reduces perspiration, more comfort. With chlorination treatment to minimise allergic reactions.



56-100 PVC Aprons

ALPHATEC® 56-100 PVC aprons are die-cut PVC fabrics that improve protection against acids, alkalis, pitting and abrasion. Sealed eyelets with 48" adjustable fasteners: Easy fit without tearing. Vinyl construction For flexible, durable personal protection.







#### BATES CARGO-PAK® &

A SIGNODE BRANI



Bates Cargo-Pak is a revolution in securing and safeguarding cargo. It is based on a simple idea: Airbags are placed in the gaps between cargo and inflated with air and are functioning as void fillers. The cargo is now secure and stabilized, and effectively protected against costly transport damages ready for the long haul. Bates Cargo-Pak is constructed with an outer material consisting of several layers of heavy-duty wet strength paper, and a strong multi-layer film inner material, giving the airbags maximum strength and ultimate airtightness.

PPW Striker is a new generation of Bates Cargo-Pak poly woven airbags, equipped with the patented Striker valve based on venturi technology. This allows for very simple and fast inflation of the airbag.



## Bates Cargo Striker Paper dunnage bag

Technical Specifications							
Size in cm		85x120	85x185	120x220			
	10cm	5.0	8.2	13.4			
Load in	20cm	2.6	5.9	9.0			
Tons in a Gap of:	35cm	0.9	1.8	3.3			
201012	45cm			2.7			
Max Gap in cm:		37	37	55			



#### MAX Inflator Mobile Air Xtreme



#### Bates Cargo Protector Paper Dunnage Bag

Size in cm		85x120	85x185	100x185	120x220
	10cm	4.9	8.1	9.4	13.2
Load in	20cm	2.5	5.6	5.8	8.8
Tons in a Gap of:	35cm	0.8	1.7	2.1	3.1
	45cm	1 4	14	1.9	2.5
Max Gap in cm:		37	37	45	55

#### Bates PPW Striker Polywoven dunnage bag





INVIZ VUMAN RA-Y

viZaar is the specialist in development of video endoscopes, and manufacturers of video endoscopes.

Visual inspection cameras are designed to serve:

power generation, chemical industry, nuclear industry, building industry, etc. Non Destructive Testing NDT, turbine inspection, tank inspection, reactor inspection, external parts retrieval and analysis are only a fractional amount of viZaar's RVI Inspection Products.

With the custom-made UV video endoscope our Remote Visual Inspection (RVI) equipment are able to execute flaw detection and identify contamination in the food industry and automotive industry.













<u>DIN ISO 5748</u>

#### KNIPEX

#### Head shape provides optimised movement when tightening steel mesh knots during reinforced concrete work

- > with cutting edges for soft and hard wire
- > also suitable for twisting and cutting binding wire
- > cutting edges additionally induction hardened, cutting edge hardness approx. 61 HRC
- > High-grade special tool steel, forged, multi stage oil-hardened






							Cu	Cutting capacities				
	EAN	<b>←→</b>								4		
Article No.	4003773-	mm		Pliers	Head	Handles	Ømm	Ø mm	Ømm	g		
68 01 160	013792	160	<b>P4</b>	black atramentized	polished		4.0	2.8	2.3	202		
68 01 180	013808	180				plastic coated	4.0	3.2	2.5	284		
68 01 200	013815	200				plastic coateu	4.0	3.5	2.8	319		
68 01 280	077664	280					4.5	4.0	3.2	467		

#### **End Cutting Nippers**

for mechanics **DIN ISO 5748** 

- > with cutting edges for soft, hard and piano wire; also suitable for thin copper wires
- > lap joint
- > cutting edges additionally induction hardened, cutting edge hardness approx. 64 HRC
- > Chrome vanadium heavy-duty steel, forged, multi stage oil-hardened





00 11 01





						Cutting capacities			Dimensions					
	EAN	<b>←→</b>								Α	В	D	С	4
Article No.	4003773-	mm	Pliers	Head	Handles	Ø mm	Ømm	Ømm	Ø mm	mm	mm	mm	mm	g
69 01 130	017974	130	black atramentized	polished	plastic coated	0.4 - 2.0	1.3	1.0	0.8	16	7.5	10	20	111
69 03 130	018001	130	chrome plated		plastic coated	0.4 - 2.0	1.3	1.0	0.8	16	7.5	10	20	111

## martor

MARTOR KG from Solingen is the leading international manufacturer and provider of high quality safety knives and safety scissors for more cutting safety. With their GS-certified safety technologies, the professional cutting tools contribute to increased occupational safety and a reduction in cutting injuries. This makes them an important part of personal protective equipment in industry, retail/logistics, trade etc.



comfortable mobility.















#### Accelerate your transformation Boost your UP time, Flexibility and productivity






## Shop smarter, Work better Find Solutions Online, Anytime

Fulfil your industrial needs with our e-commerce platform!



www.industrialsolution.ae




Products


Authorized Distributor of best quality Brands: 3M, Deltaplus, Nitto Kohki, Ansell, Orbitalum, Graco, and more!

Get it fast 1-day delivery!

Streamlined checkout, secure and convenient online payments.

Explore the future of industrial shopping today on our website!









PO Box 19227, Dubai - United Arab Emirates

Tell: +971 4347 4444

E Mail: info@mef.ae | industrial@mef.ae

Web: www.mef.ae | www.industrialsolution.ae











